

**80-1000MHz/80Watt/Module**

The model KB00810M49A is a multi-octave high power amplifier operating between 80 MHz and 1000 MHz and offering a wide dynamic Range with 80 Watts typical saturated power. The employment of advanced high power devices in manufacturing ensures this module exceptional power performance, long term reliability and high efficiency. It is ideal for multi-octave broadband high power RF, S Band applications.

**Model Number: KB00810M49A**
**FEATURES:**

- Broadband & High power;
- High Efficiency;
- Small Size & Light Weight;
- Low Distortion

**ELECTRICAL SPECIFICATIONS @ +28.0VDC, 25°C, 50Ω**

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	80		1000	MHz
RF Output Power	Pout		80		Watt
Power Gain	Gp		49		dB
Small Signal Gain Flatness	$\Delta G_{ss}$		$\pm 2$		dB
Input Return Loss	S11			-10	dB
Harmonics @50W	H		-15	-10	dBc
Spurious Signals	Spur		-60		dBc
In/Output Impedance	Impedance		50		$\Omega$
Operating Voltage	VDC		28		Volt
DC Current @80W	IDD		9.5	11	Amp

**MECHANICAL SPECIFICATIONS**

Parameter	Value	Units	Notes
Dimensions	150x 90 x 25 [5.91x3.54x0.98]	mm [inch]	Maximum
Weight	1.5 [3.3]	kg [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	D-Sub 9-Pin, Male		
Cooling	External Heatsink Required (Not Supplied)		

**ENVIRONMENTAL CHARACTERISTICS (Design to Meet)**

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-25		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

**Absolute Maximum Rating**

Input RF drive level without damage	+10 dBm (Max)
Load VSWR @ POUT =50W	$\infty$ @ all load phase & amplitude for duration of 1 minutes; 3:1 @ all load phase & amplitude continuous
Over Temperature	85°C @ heatsink [restored @ 60°C]

*Focus on Your Application*

**\*Chengdu KeyLink Microwave Technology Co., Ltd.\***

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761\*8708 >> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com >> www.keylinkmw.com

*Specifications subject to change without notice*


80-1000MHz/80Watt/Module

Model Number: KB00810M49A


**DC INTERFACE CONNECTOR**

Pin #	Description	Specifications
1,6,7	VDD	28VDC
8,9	GND	Ground
5	SHUTDOWN	Amplifier Disable: TTL Logic High (3.3V) (Internally Pulled-Low)
2	CURRENT SENSE	Analog voltage relative to IDD @ 100mV per Ampere
3	TEMP SENSE	Analog voltage relative to Module's Temperature @ 10 mV/°C
4	NC	No electrical connection

**OUTLINE DRAWING (All dimensions in mm [inch])**



**TYPICAL PERFORMANCE PLOTS ( For Reference Only)**



Note:

1. Adequate heatsink required.
2. This product will be developed upon contract/order. All the above specs are for reference only. Actual product may be different. Please check with KeyLink sales team if you have any question.

*Focus on Your Application*

**\*Chengdu KeyLink Microwave Technology Co., Ltd.\***

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761\*8708 >> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice